3099999 | 050T110 EMPTY DUCT



ConQuest® Empty Conduit, 1/2 in, SDR 11, terracotta

Product Classification

Product TypeEmpty conduitProduct BrandConQuest®

General Specifications

ColorTerracottaConduit TypeNon-toneableDensity Test MethodASTM D792A

 Density, maximum
 0.955 g/cm³ | 0.035 lb/in³

 Density, minimum
 0.941 g/cm³ | 0.034 lb/in³

Design Standard ASTM D3350-05

Wall Type Smooth

Dimensions

Length 304.8 m | 1000 ft

Inner Diameter, nominal16.967 mm | 0.668 inOuter Diameter, nominal21.336 mm | 0.84 in

Wall Thickness Designation SDR 11

Wall Thickness, minimum 1.93 mm | 0.076 in

Nominal Size 1/2 in

Material Specifications

Flexural Modulus, minimum 551.581 N/mm² | 80000 psi

Flexural Property Test Method ASTM D790

Hydrostatic Design BasisNot pressure rated

Hydrostatic Design Test MethodASTM D2837

Material Type High density polyethylene (HDPE)

Melt Flow Rate Test Method ASTM D1238

Page 1 of 2



3099999 | 050T110 EMPTY DUCT

Melt Flow Rate, maximum 0.39 g/10 min

Mechanical Specifications

Minimum Bend Radius, unsupported 254 mm | 10 in

Tensile Property Test Method ASTM D638

Tensile Strength at yield, minimum 20.684 N/mm² | 3000 psi

Pulling Tension, maximum 176.901 kg | 390 lb

Environmental Specifications

Environmental Stress Crack Resistance Failure rate of 10% within 96 hours

Environmental Stress Test Method ASTM D1693, ESCR Condition B

Packaging and Weights

Weight, net 126.494 kg/km | 85 lb/kft

Regulatory Compliance/Certifications

Agency Classification

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system



* Footnotes

Environmental Stress Crack Resistance ESCR—Environmental Stress Crack Resistence

