E63589-000 | F0SC450-6DBX1521NN2T-U23



FOSC® 450/B Fiber Optic Splice Closure, Gel Cable sealing, with integrated DWDM, 8 channels + upgrade port, double demux, 2 test ports

- Single-ended, O-ring sealed dome closure for splicing feeder and distribution cables
- Gel cable sealing technology allows easy adding or removing of a wide size range of cables
- Compatible with most common cable types: e.g. loose tube, central core, ribbon fiber
- FOSC splice trays hinged for access to any splice without disturbing other trays
- Closure can be used in aerial, pedestal and underground (up to 5 meters) environments
- Compatible with CommScope's CWDM modules and optical splitter trays

Product Classification

Regional AvailabilityLatin America| North AmericaProduct TypeSingle-ended, round fiber closure

Product Brand FOSC®
Product Series FOSC 450

General Specifications

Cable Entry Drop Port StyleRoundCable Entry Main Port StyleRound

Cable Ports Quantity, total6 round portsCable Sealing TypeCompressed gel

Closure Sealing Type Dome-to-base clamp with O-ring

Closure Style Single-ended

ColorBlackFlash Test ValveNoneGround Feed-throughNone

Mounting Pole | Strand | Wall

Network Area Type Feeder

Splice Tray Included, quantity 6

Splicing Type, Supported Mass fusion | Single fusion

Dimensions

Length 610 mm | 24.016 in **Diameter** 180 mm | 7.087 in

COMMSC PE°

E63589-000 FOSC450-6DBX1521NN2T-U23

232 mm | 9.134 in Diameter, with clamp 25 mm | 0.984 in Main Cable Diameter, maximum

Material Specifications

Material Type Impact-resistant polymer

Environmental Specifications

Environmental Space Below ground | Buried **Qualification Standards** IEC 61300, 5 m waterhead

Packaging and Weights

Included Multiplexer (2)

Packaging quantity

Packaging Type Box | Carton Weight, net 5.5 kg | 12.125 lb

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Below maximum concentration value

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system **REACH-SVHC** Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant **UK-ROHS** Compliant





