FDT-BJ024NXT2000

iFDT Indoor Fiber Distribution Terminal, 24-fiber, SC/APC, loose tube OSP cable, 2000 feet

- Compact and secure family of enclosures by connecting fiber cables at MDUs
- Integrated splice trays offer flexible splice management for individual or mass splicing
- Dual-hinged design ensures separation of owner/client network segments
- Robust steel construction protects fibers against damage and ensures network reliability
- Slotted cable entrance ports allow for rapid cable installation and pass-through capability

Product Classification

Regional Availability	North America
Product Type	Fiber distribution terminal
Product Series	IFDT

General Specifications

Adapters, quantity	24
Cable Entry Location	Bottom right	Top right
Cable Type	OSP - Loose Tube
Color	Putty white
Front Door Type	Double hinged
Growth Configuration	Fully loaded
Interface	SC/APC
Interface, stub	No connector
Lock Type	Padlock ready
Mounting	Wall
Port, quantity	24

Dimensions

Height	203.2 mm	8 in
Width	355.6 mm	14 in
Depth	127 mm	5 in
Cable Length	609.6 m	2000 ft

Ordering Tree

COMMSCOPE®

FDT-BJ024NXT2000

FDT- __ __ __ __ __ NX __ __ __ __ 0

Enclosure Type/Capacity

A	iFDT-12	12 Fiber
B	iFDT-24	24 Fiber
C	iFDT-48	48 Fiber
D	iFDT-72	72 Fiber
E	iFDT-96	96 Fiber

Connector/Adapter Style

Singlemode		
J	SC/APC	
N	SC/UPC	
K	LC/UPC	
Multimode		
9	MMSC	
6	MMLC	

Splice Tray

0	No Tray
2	Heat Shrink Fusion
3	Mechanical/Ribbon

Fiber Count

06	6 Fiber
12	12 Fiber
24	24 Fiber
48	48 Fiber
72	72 Fiber
96	96 Fiber

Stub Length

000	0 Feet
025	25 Feet
100	100 Feet
200	200 Feet
300	300 Feet
500	500 Feet

Cable Type

Pigtails	
A	Bare ribbon pigtail assy
B	12 Fiber Soft-Walled Bundle*
Stubs	
S	Ribbon OSP w/Conn
R	Ribbon IFC w/Conn
T	Loose Tube OSP w/Conn
V	Loose Tube IFC w/Conn

* 900 micron fiber bundled in a soft jacket.

Material Specifications

Finish	Powder coated
Material Type	Steel

Optical Specifications

Fiber Mode	Singlemode

Environmental Specifications

Environmental Space	Indoor
Qualification Standards	NEMA, Type 12 | Telcordia GR-2898-CORE

Packaging and Weights

Packaging quantity	1

COMMSCOPE®

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Above maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant/Exempted
UK-ROHS	Compliant/Exempted

COMMSCOPE®