

NG4access® Module VAM, Splitter, 1x2, symmetrical split, singlemode, LC /APC, front, left, 8 circuits

- VAMs help enhance optical transport systems by providing flexible, easy to incorporate optical components into the network
- VAMs increase fiber capacity and help troubleshooting or distributing signals to multiple subscribers
- *Product complies with the Build America, Buy America Act (BABAA) requirements of the Infrastructure Investment and Jobs Act of 2021 (Pub. L. 117- 58, §§ 70901-70953), or is the subject of a waiver approved by the Secretary of Commerce or designee. Compliance requirements and waiver applicability vary based on government funding program. Check the laws and regulations for your specific program.

Product Classification

| Regional Availability | Asia Australia/New Zealand China EMEA India Latin America North America |
|------------------------|--|
| Portfolio | CommScope® |
| Product Type | Splitter module |
| Product Brand | NG4access® |
| Product Series | FACT NG4 |
| Government Funding | Build America Buy America (BABA) compliant* |
| General Specifications | |
| Device Type | Plug-and-play module |
| Functionality | Splitting |
| Technology Type | Planar lightwave circuit (PLC) |
| Access | Front |
| Application | For use with NG4 access frames |
| Distribution Type | 1 x 2 splitter |
| Interface, front | LC/APC |
| Interface, Input | LC/APC |
| Interface, Output | LC/APC |
| Split Ratio | Symmetrical |
| Splitter, quantity | 8 |
| Tray Orientation | Left orientation |
| | |

Page 1 of 2

©2024 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: April 11, 2024



NG4-VSMLF8C

Dimensions

| Height | 13.21 mm 0.52 in |
|--------|---------------------|
| Width | 159.77 mm 6.29 in |
| Depth | 130.3 mm 5.13 in |

Optical Specifications

| Directivity, minimum | 55 dB |
|--------------------------------------|-------------------------|
| Performance Grade | Grade O (PLC, low loss) |
| Polarization Dependent Loss, maximum | 0.15 dB |
| Uniformity, maximum | 0.85 dB |
| Wavelength Range | 1260-1650 nm |
| Insertion Loss, Splitter, maximum | 4.2 dB |
| Return Loss, Connector, minimum | 55 dB |

Packaging and Weights

| Packaging quantity | |
|--------------------|--|
|--------------------|--|

Regulatory Compliance/Certifications

| Agency | Classification |
|------------|---|
| CHINA-ROHS | Above maximum concentration value |
| REACH-SVHC | Compliant as per SVHC revision on www.commscope.com/ProductCompliance |
| ROHS | Compliant/Exempted |
| UK-ROHS | Compliant/Exempted |

1



Page 2 of 2

©2024 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see https://www.commscope.com/trademarks. All product names, trademarks and registered trademarks are property of their respective owners. Revised: April 11, 2024

