760237224 | CM24-2X6-LS-ULL



G2 ULL 2x6 Multimode OM4 Conversion Module, (2) MPO-24 unpinned ports rear, (6) MPO-8 pinned front

Product Classification

Regional Availability

Asia | Australia/New Zealand | EMEA | Latin America | North America

 Portfolio
 CommScope®

 Product Type
 Fiber module

 Product Brand
 SYSTIMAX ULL

General Specifications

Functionality Breakout

Adapters, quantity, front 6
Adapters, quantity, rear 2
Color, front Aqua

Color, rear Aqua

Data Module Type Fiber Conversion Module

Interface, front MPO

Interface Feature, front Standard

Interface, rear MPO

Interface Feature, rear Key up | Unpinned

Polarity Method B Enhanced (ULL)

Shuttered No Total Fibers, quantity 48

Total Ports, quantity, front 6

Dimensions

 Height
 26.42 mm | 1.04 in

 Width
 96.52 mm | 3.8 in

COMMSCOPE®

760237224 | CM24-2X6-LS-ULL

Depth 117.35 mm | 4.62 in

Optical Specifications

Fiber Mode Multimode

Fiber Type OM4, LazrSPEED® 550

Insertion Loss, maximum 0.4 dB

Environmental Specifications

Safety Standard cUL US 1863

Packaging and Weights

Packaging quantity

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Above maximum concentration value

ISO 9001:2015 Designed, manufactured and/or distributed under this quality management system

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant/Exempted UK-ROHS Compliant/Exempted

