

760242972 | 360DMiP-24LC-SM

InstaPATCH® 360 TeraSPEED® Standard Module, 24 LC fibers (12 duplex ports), Blue, iPatch Ready



Product Classification

| | |
|------------------------------|---|
| Regional Availability | Asia Australia/New Zealand EMEA Latin America North America |
| Portfolio | CommScope® |
| Product Type | Fiber module |

General Specifications

| | |
|-------------------------------------|----------------------------|
| Functionality | Breakout |
| Adapters, quantity, front | 12 |
| Adapters, quantity, rear | 2 |
| Color, front | Blue |
| Color, rear | Gray |
| Data Module Type | Standard |
| Intelligence Type | iPatch® ready |
| Interface, front | LC/UPC |
| Interface, rear | MPO |
| Interface Feature, rear | Pinned Reduced footprint |
| Shuttered | Yes |
| Total Fibers, quantity | 24 |
| Total Ports, quantity, front | 24 |

Dimensions

| | |
|---------------|--------------------|
| Height | 30.48 mm 1.2 in |
| Width | 91.44 mm 3.6 in |
| Depth | 116.84 mm 4.6 in |

Optical Specifications

| | |
|---|--|
| Fiber Mode | Singlemode |
| Fiber Type | G.652.D and G.657.A1, TeraSPEED® OS2 |
| Insertion Loss Change, mating | 0.3 dB |
| Insertion Loss Change, temperature | 0.3 dB |
| Insertion Loss, maximum | 1.05 dB |

Environmental Specifications

| | |
|------------------------|----|
| Safety Standard | UL |
|------------------------|----|

Packaging and Weights

| | |
|---------------------------|---|
| Packaging quantity | 1 |
|---------------------------|---|

Regulatory Compliance/Certifications

| Agency | Classification |
|---------------|--|
| CHINA-ROHS | Below maximum concentration value |
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| REACH-SVHC | Compliant as per SVHC revision on www.commscope.com/ProductCompliance |
| ROHS | Compliant |
| UK-ROHS | Compliant |



* Footnotes

| | |
|---|---|
| Insertion Loss Change, mating | Maximum insertion loss change after 500 matings |
| Insertion Loss Change, temperature | Maximum insertion loss change from -10 °C to +60 °C (+14 °F to +140 °F) |