

A19964-000 | FOMS-FPS-0-SKS1-24

FOMS-FPS Fiber Termination/Splice Panel, 24 SC/UPC, singlemode, 1RU, 19 in, gray

Product Classification

Regional Availability	EMEA
Portfolio	CommScope®
Product Type	Fiber patch/splice panel
Product Series	FOMS-FPS

General Specifications

Functionality	Patching Splicing
Color	Gray
Color, front	Gray
Interface, front	SC/UPC
Rack Type	EIA 19 in EIA 23 in ETSI 600 mm
Rack Units	1
Shelf Movement	Hinged
Total Ports, quantity	24

Dimensions

Height	44.45 mm 1.75 in
Width	482.6 mm 19 in

Ordering Tree

A19964-000 | FOMS-FPS-O-SKS1-24

FOMS-FPS - X - X X XX - XX

Chassis type				Number of pigtails and/or connector ports							
<input type="radio"/>	19" - 44 mm high			48	(for LC and MU only)						
Shelf type				24							
<input type="radio"/>	Patching only (jumpers, break-out cable)			16	(not for LC and MU)						
<input type="radio"/>	Splicing and patching (loose tube cable, ribbon, IFC)			12	(not for LC and MU)						
				0							
Tray type/pigtails				Connector adapter with retainer							
Secondary coated pigtails included		Splice protector		Jumpers leave shelf		NN No connectors/pigtails					
				Right front		Left front					
Not applicable (patching only)				N		M					
No		SMOUV*		E		G					
No		ANT*		F		H					
Yes		SMOUV*		I		K					
Yes		ANT*		J		L					
								Min.return loss			
								SC FC E2000 LC DIN ST MU			
								Single Mode Standard			
								45 dB (PC)			
								50 dB (UPC)			
								60 dB (APC 8°)			
								60 dB (APC 9°)			
								Single Mode Low Loss			
								50 dB (UPC)			
								60 dB (APC 8°)			
								60 dB (APC 9°)			
								Single Mode Consumer Grade			
								50 dB (UPC)			
								60 dB (APC 8°)			
								Multi Mode			
								50/900 μ			
								62.5/900 μ**			

* Splice protectors not included in the kit
 ** In case of adapters only (no pigtails included) use S5D, F5D, E5D, L5D and T5D.

Material Specifications

Material Type Ethylene-propylene (EP) | Polyethylene terephthalate (PET)

Optical Specifications

Fiber Mode Singlemode

Packaging and Weights

Included Mounting hardware

Packaging quantity 1

Regulatory Compliance/Certifications

Agency	Classification
CHINA-ROHS	Below maximum concentration value
REACH-SVHC	Compliant as per SVHC revision on www.commscope.com/ProductCompliance
ROHS	Compliant
UK-ROHS	Compliant

