FFC-24



Fiber Optic Entrance Cabinet, 24 Drawers, Wall mounted

- Provides splicing, administration and storage for outside plant (OSP) and intrafacility cables (IFC)
- Offers a cost-effective, space-saving alternative to splicing on the fiber frame
- Cabinets are designed for deployment in a building equipment area
- Bend radius protection and discrete subunit routing paths ensure easy installation
- Can deploy high count of stranded or ribbon fiber cables
- Ultra high density splice capacity dependent on splice tray used

Product Classification

Regional Availability Latin America | North America

Product Type Fiber entrance cabinet

Product Series FEC

General Specifications

Access Front

Cable Entry LocationBottom| Side| TopCable Exit LocationBottom| Side| Top

Color Putty white

MountingWallSplice Drawers, quantity24Splice Trays Included, quantity0

Splicing Capacity Note 24 times number of splices per tray (example 24x288 = 6912)

Dimensions

 Height
 1143 mm | 45 in

 Width
 812.8 mm | 32 in

 Depth
 330.2 mm | 13 in

Environmental Specifications

Environmental Space Indoor

Packaging and Weights

Included Grommets

COMMSC PE°

FEC-24

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Above maximum concentration value

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant/Exempted UK-ROHS Compliant/Exempted

