114692-000 | TTRC-250-A734

TTRC Copper Closure, unpressurized, gel sealed, 510 mm sheath opening, for up to 300 pair splices

- Watertight, toolless, torchless and re-usable closure for aerial applications
- Seals unpressurised inline splices in new construction and network maintenance applications up to 600 pairs
- Sealing on both the closure body and a multiple of cables is performed by compressing the gel material between two plastic flanges
- Gel compression is activated by a built-in tensioning mechanism

OBSOLETE

This product was discontinued on: June 30, 2022

Product Classification

Regional Availability EMEA

Product Type Gel sealed closure

Product Series TTRC

General Specifications

Application For use with Polyethylene cables

Cable Capacity, maximum 1

Cable Sealing TypeGel filledClosure StyleIn-lineColorBlackMountingStrand

Dimensions

Single Cable Diameter, maximum42 mm | 1.654 inSingle Cable Diameter, minimum26 mm | 1.024 inSplice Bundle Diameter, maximum92 mm | 3.622 inSheath Opening, nominal510 mm | 20.079 in

Environmental Specifications



114692-000 | TTRC-250-A734

Environmental Space Aerial

Packaging and Weights

Packaging quantity 1

Packaging Type Bag | Carton

Regulatory Compliance/Certifications

Agency Classification

CHINA-ROHS Below maximum concentration value

REACH-SVHC Compliant as per SVHC revision on www.commscope.com/ProductCompliance

ROHS Compliant UK-ROHS Compliant

