F4A-DMDR-8M-P-SGW



HELIAX® 1/2" Superflexible SureFlex® Jumper with interface types 7-16 DIN Male and 7-16 DIN Male Right Angle with HELIAX® SureGuard weatherproofing, 8 m $\,$

• If there are threads along the entire device port length, the HELIAX® SureGuard weatherproofing solutions will only seal properly if the HSG-M29-ADPT adapter is installed on the device port

Product Classification

Product Type SureFlex® Premium, static PIM

Product Brand HELIAX® | SureFlex®

Product Series RSJ4-50

General Specifications

Body Style, Connector AStraightBody Style, Connector BRight angleInterface, Connector A7-16 DIN MaleInterface, Connector B7-16 DIN Male

Specification Sheet Revision Level B

Dimensions

Length 8 m | 26.247 ft

Nominal Size 1/2 in

Electrical Specifications

3rd Order IMD Static -116 dBm

3rd Order IMD Static Test Method Two +43 dBm carriers

DTF, Connector A -34 dB

DTF, Connector B -32 dB

VSWR/Return Loss

Frequency Band	VSWR	Return Loss (dB)
2.2-2.7 GHz	1.135	23.98
698-960 MHz	1.101	26.36
1700-2200 MHz	1.101	26.36

Page 1 of 3



F4A-DMDR-8M-P-SGW

3400-3800 MHz

1.222

20.01

Jumper Assembly Sample Label



Environmental Specifications

Immersion Test MethodMeets IEC 60529:2001, IP68 in mated condition

Weatherproofing Method HELIAX® SureGuard weatherproofing boot

Packaging and Weights

Included Weatherproofing boot

Compliant/Exempted

Regulatory Compliance/Certifications

AgencyClassificationCHINA-ROHSBelow maximum concentration valueISO 9001:2015Designed, manufactured and/or distributed under this quality management systemREACH-SVHCCompliant as per SVHC revision on www.commscope.com/ProductComplianceROHSCompliant



UK-ROHS

Included Products

COMMSCOPE®

F4A-DMDR-8M-P-SGW

HSG-FSJ4-DR

 HELIAX® SureGuard® Boot for 1/2 in right angle jumpers to antennas or devices

