

# ACCURET-A20



## Actuator, AISG 2.0 default protocol

- Connects to the base station antenna for remote electrical tilt
- Easy to install; no tools required
- Easily mounts to back of antenna
- Factory set to AISG 2.0 mode

### OBSOLETE

This product was discontinued on: March 31, 2023

## Product Classification

**Product Type** RET actuator

## General Specifications

**AISG Input Connector** 8-pin DIN Male  
**AISG Input Connector Quantity** 1  
**AISG Output Connector** 8-pin DIN Female  
**AISG Output Connector Quantity** 1  
**Color** Black

## Dimensions

**Height** 205 mm | 8.071 in  
**Width** 125 mm | 4.921 in  
**Depth** 50 mm | 1.969 in

## Electrical Specifications

**Input Voltage** 10–30 Vdc  
**Adjustment Cycles, minimum** 10000 cycles  
**Adjustment Time, full range, maximum** 30 s  
**Default Protocol** AISG 2.0  
**Electromagnetic Compatibility (EMC)** CFR 47 Part 15, Subpart B, Class A | EN 55022  
**Interface Protocol Signal** RS-485

# ACCURET-A20

---

<b>Lightning Surge Capability</b>	5 times @ -10 kA   5 times @ 10 kA
<b>Lightning Surge Capability Test Method</b>	IEC 61000-4-5
<b>Lightning Surge Capability Waveform</b>	1.2/50 voltage and 8/20 current combination waveform
<b>Lightning Surge Test Mode</b>	Common mode
<b>Protocol</b>	AISG 2.0

## Material Specifications

<b>Material Type</b>	ABS
----------------------	-----

## Environmental Specifications

<b>Operating Temperature</b>	-40 °C to +70 °C (-40 °F to +158 °F)
<b>Climatic Sequence Test Method</b>	IEC 60068-2-14
<b>Cold Exposure Test Method</b>	IEC 60068-2-1
<b>Corrosion Test Method</b>	IEC 60068-2-11, Test Condition Ka   IEC 60068-2-52, Test Condition Kb
<b>Damp Heat Exposure Test Method</b>	IEC 60068-2-30, Test Condition Db
<b>Heat Exposure Test Method</b>	IEC 60068-2-2
<b>Ingress Protection Test Method</b>	IEC 60529:2001, IP56
<b>Packaged Product Shock Test Method</b>	ASTM D4169   GR-63-CORE, Section 4.1.1
<b>Rain Simulation Test Method</b>	IEC 60068-2-18, Test Condition Ra, Method 1
<b>UV Resistance Test Method</b>	IEC 60068-2-5, Test Condition B
<b>Vibration Test Method</b>	ASTM D4169   IEC 60068-2-6

## Packaging and Weights

<b>Weight, net</b>	0.5 kg   1.102 lb
--------------------	-------------------

## Regulatory Compliance/Certifications

<b>Agency</b>	<b>Classification</b>
CE	Compliant with the relevant CE product directives
CHINA-ROHS	Above maximum concentration value
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
ROHS	Compliant/Exempted
UK-ROHS	Compliant/Exempted



# ACCURET-A20

---